

Declaration of Performance

No. 001/CPR/2013-07-01

Product(s): Purus Air Admittance Valves: Purus AAV 40/50

Manufacturer:

Purus AB Södra Dragongatan 15 SE-271 39 Ystad Sweden

System of assessment and verification of constancy of performance: System 4.

Declared performance:

Deciared periormanee.		
Essential caracteristics	Performance	Harmonized technical specification
Airtightness	Class A	EN 12380 5.3
Durability	Designation I	EN 12380 5.4
Effectiveness (airflow)	11,3 l/s	EN 12380 5.5
Effectiveness (opening pressure)	Pass	EN 12380 5.5
Effectiveness at temperatures below zero	Pass	EN 12380 5.5

The performance of the **Product(s)** identified above is in conformity with the **Declared performance** above. This declaration of performance is issued under the sole responsibility of the **Manufacturer** above.

Signed for and on behalf of the manufacturer by:

Vstad 2013-07-01 (Place/Date of issue)

(Signature)

(name and function)



Declaration of Performance

No. 003/CPR/2013-07-01

Product(s): Purus Air Admittance Valves: Purus AAV 110

Manufacturer:

Purus AB Södra Dragongatan 15 SE-271 39 Ystad Sweden

System of assessment and verification of constancy of performance: System 4.

Declared performance:

Deciared performance.			
Essential caracteristics	Performance	Harmonized technical specification	
Airtightness	Class B	EN 12380 5.3	
Durability	Designation I	EN 12380 5.4	
Effectiveness (airflow)	78,6 l/s	EN 12380 5.5	
Effectiveness (opening pressure)	Pass	EN 12380 5.5	
Effectiveness at temperatures below zero	Pass	EN 12380 5.5	

The performance of the **Product(s)** identified above is in conformity with the **Declared performance** above. This declaration of performance is issued under the sole responsibility of the **Manufacturer** above.

Signed for and on behalf of the manufacturer by:

(Place/Date of issue)

(Signature)

HÁKAN LARSSON/TRCHNICAL MGR. (name and function)



Declaration of Performance

No. 002/CPR/2013-07-01

Product(s): Purus Air Admittance Valves: Purus AAV 75

Manufacturer:

Purus AB Södra Dragongatan 15 SE-271 39 Ystad Sweden

System of assessment and verification of constancy of performance: System 4.

Declared performance:

Decial ou per les maries.	beclared performance:		
Essential caracteristics	Performance	Harmonized technical specification	
Airtightness	Class B	EN 12380 5.3	
Durability	Designation I	EN 12380 5.4	
Effectiveness (airflow)	34,8 l/s	EN 12380 5.5	
Effectiveness (opening pressure)	Pass	EN 12380 5.5	
Effectiveness at temperatures below zero	Pass	EN 12380 5.5	

The performance of the **Product(s)** identified above is in conformity with the **Declared performance** above. This declaration of performance is issued under the sole responsibility of the **Manufacturer** above.

Signed for and on behalf of the manufacturer by:

(Place/Date of issue)

(Signature)

(name and function)